

CESIPC

EPC Industrial Panel PC Series Brochure



mini pc



panel pc



industrial pc



tablet pc



IP67 Panel pc



rugged laptop

- 10inch Panel PC (EPC-S10X2A)
- 12inch Panel PC (EPC-S12X2A)
- 15inch Panel PC (EPC-S15X2A)
- 15inch Panel PC (EPC-S1522B)
- 17inch Panel PC (EPC-S17X2A)
- 19inch Panel PC (EPC-S19X2A)
- 12.5inch Panel PC (EPC-W12X2A)
- 13.3inch Panel PC (EPC-W13X2A)
- 15.6inch Panel PC (EPC-W15X2A)
- 18.5inch Panel PC (EPC-W18X2A)
- 21.5inch Panel PC (EPC-W21X2A)
- 23.6inch Panel PC (EPC-W24X2A)

[Click to Top](#) 10 INCH

► Introduction

The EPC-S10X2A series industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers versatile configuration options, equipped with onboard Intel® Celeron or advanced 10th/12th Gen Core™ i3/i5/i7 processors, delivering superior performance. Engineered for reliability, the EPC-S10X2A ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored

► Product Image



► System Core

CPU	Celeron J1900	Celeron J6412	I3-10110U	I5-10210U	I7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

► I / O Ports

CPU	Celeron J1900	Celeron J6412	I3-10110U	I5-10210U	I7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0/ Type A	5	4	2	2	2	2	2	2
USB 3.0/ Type A	1	2	4	4	4	4	4	4
RS232/ DB9	2	2	2	2	2	2	2	2
RS485/ DB9	1	1	1	1	1	1	1	1
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

► Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

► Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

► Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

► OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

► Mechanical

Dimension	262.2(W)×209.4(D)×70.6(H)mm
Cutout Size	241.5×186.0mm
Weight	KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

► Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

► Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

► LCD Panel

LCD Size	9.7 inch Panel Size
Resolution	1024 x 768 / 4:3
Brightnesss (cd/m ²)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)

[Click to Top](#) 12 INCH

► Introduction

The EPC-S12X2A series industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers versatile configuration options, equipped with onboard Intel® Celeron or advanced 10th/12th Gen Core™ i3/i5/i7 processors, delivering superior performance. Engineered for reliability, the EPC-S12X2A ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored

► Product Image



► System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

► I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0/ Type A	5	4	2	2	2	2	2	2
USB 3.0/ Type A	1	2	4	4	4	4	4	4
RS232/ DB9	2	2	2	2	2	2	2	2
RS485/ DB9	1	1	1	1	1	1	1	1
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

► Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Bootling	1x AT/ATX Mode Switch (Internal settings)

► Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

► Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

► OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

► Mechanical

Dimension	299.0(W)×237.5(D)×74.6(H)mm
Cutout Size	277.9×222.7mm
Weight	KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

► Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

► Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

► LCD Panel

LCD Size	12 inch Panel Size
Resolution	1024 x 768 / 4:3
Brightness (cd/m ²)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)

[Click to Top](#) 15 INCH

► Introduction

The EPC-S15X2A series industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers versatile configuration options, equipped with onboard Intel® Celeron or advanced 10th/12th Gen Core™ i3/i5/i7 processors, delivering superior performance. Engineered for reliability, the EPC-S15X2A ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored

► Product Image



► System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

► I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0/ Type A	5	4	2	2	2	2	2	2
USB 3.0/ Type A	1	2	4	4	4	4	4	4
RS232/ DB9	4	4	4	4	4	4	4	4
RS485/ DB9	2	2	2	2	2	2	2	2
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

► Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

► Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

► Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

► OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

► Mechanical

Dimension	359.9(W)×283.9(D)×75.1(H)mm
Cutout Size	342.4×269.4mm
Weight	KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

► Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

► Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

► LCD Panel

LCD Size	15 inch Panel Size
Resolution	1024 x 768 / 4:3
Brightness (cd/m ²)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)

[Click to Top](#)

15 INCH

► Introduction

EPC-S1522B is a high-performance 15-inch industrial PC with a fanless design, supporting Intel® 12th Gen Core™ i3/i5/i7 processors. It features five Gigabit LAN ports, rich I/O connectivity, and strong system expandability. Designed for demanding environments such as semiconductor, machine vision, AGV, medical imaging, and energy automation, the EPC-S1522B integrates CESIPC's intelligent thermal control and hot-swappable fans for stable operation under high-load conditions.

► Product Image



- ★ Intel® 12th Gen Core™ processor support
- ★ Five Gigabit LAN ports and versatile I/O

- ★ Intelligent thermal control with hot-swappable fan
- ★ Perfect for semiconductor and machine vision

► System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

► I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0	5	4	2	2	2	2	2	2
USB 3.0	1	2	4	4	4	4	4	4
RS232	3	3	3	3	3	3	3	3
RS485	/	/	/	/	/	/	/	/
VGA	/	/	/	/	/	/	/	/
HDMI	1	1	1	1	1	1	1	1
Ethernet	5 x Intel I210	5 x Intel I210	5 x Intel I210	5 x Intel I210	5 x Intel I210	5 x Intel I210	5 x Intel I210	5 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

► Power Supply

DC Input	1×2-pin Aviation Power Connector for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Bootling	1x AT/ATX Mode Switch (Internal settings)

► Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

► Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

► OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

► Mechanical

Dimension	359.9(W)×283.9(D)×75.1(H)mm
Cutout Size	342.4×269.4mm
Weight	7 KG G.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

► Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

► Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

► LCD Panel

LCD Size	15 inch Panel Size
Resolution	1024 x 768 / 4:3
Brightness (cd/m ²)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)

[Click to Top](#)

17 INCH

► Introduction

The EPC-S17X2A series industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers versatile configuration options, equipped with onboard Intel® Celeron or advanced 10th/12th Gen Core™ i3/i5/i7 processors, delivering superior performance. Engineered for reliability, the EPC-S17X2A ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored

► Product Image



▶ System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

▶ I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0/ Type A	5	4	2	2	2	2	2	2
USB 3.0/ Type A	1	2	4	4	4	4	4	4
RS232/ DB9	4	4	4	4	4	4	4	4
RS485/ DB9	2	2	2	2	2	2	2	2
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

▶ Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

▶ Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

► Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

► OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

► Mechanical

Dimension	397.0(W)×321.0(D)×75.1(H)mm
Cutout Size	374.6×312.6mm
Weight	KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

► Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

► Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

► LCD Panel

LCD Size	17 inch Panel Size
Resolution	1280 x 1024 / 4:3
Brightnesss (cd/m2)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)

[Click to Top](#)

19 INCH

► Introduction

The EPC-S19X2A series industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers versatile configuration options, equipped with onboard Intel® Celeron or advanced 10th/12th Gen Core™ i3/i5/i7 processors, delivering superior performance. Engineered for reliability, the EPC-S19X2A ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored

► Product Image



▶ System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

▶ I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0/ Type A	5	4	2	2	2	2	2	2
USB 3.0/ Type A	1	2	4	4	4	4	4	4
RS232/ DB9	4	4	4	4	4	4	4	4
RS485/ DB9	2	2	2	2	2	2	2	2
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

▶ Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

▶ Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

▶ Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

▶ OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

▶ Mechanical

Dimension	443.0(W)×368.0(D)×75.1(H)mm
Cutout Size	411.9×342.9mm
Weight	KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

▶ Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

▶ Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

▶ LCD Panel

LCD Size	19 inch Panel Size
Resolution	1280 x 1024 / 4:3
Brightness (cd/m ²)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)

[Click to Top](#)

12.5 INCH

► Introduction

The EPC-W12X2A series industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers versatile configuration options, equipped with onboard Intel® Celeron or advanced 10th/12th Gen Core™ i3/i5/i7 processors, delivering superior performance. Engineered for reliability, the EPC-W12X2A ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored

► Product Image



► System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

► I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0/ Type A	5	4	2	2	2	2	2	2
USB 3.0/ Type A	1	2	4	4	4	4	4	4
RS232/ DB9	2	2	2	2	2	2	2	2
RS485/ DB9	1	1	1	1	1	1	1	1
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

► Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

► Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

► Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

► OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

► Mechanical

Dimension	327.5(W)×206.5(D)×70.6(H)mm
Cutout Size	307.4×190.0mm
Weight	KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

► Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

► Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

► LCD Panel

LCD Size	12.5 inch Panel Size
Resolution	1920×1080 16:9
Brightness (cd/m ²)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)

[Click to Top](#)

13.3 INCH

► Introduction

The EPC-W13X2A series industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers versatile configuration options, equipped with onboard Intel® Celeron or advanced 10th/12th Gen Core™ i3/i5/i7 processors, delivering superior performance. Engineered for reliability, the EPC-W13X2A ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored

► Product Image



▶ System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

▶ I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0/ Type A	5	4	2	2	2	2	2	2
USB 3.0/ Type A	1	2	4	4	4	4	4	4
RS232/ DB9	2	2	2	2	2	2	2	2
RS485/ DB9	1	1	1	1	1	1	1	1
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

▶ Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

▶ Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

▶ Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

▶ OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

▶ Mechanical

Dimension	345.2(W)×215.6(D)×74.6(H)mm
Cutout Size	325.1×195.5mm
Weight	KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

▶ Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

▶ Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

▶ LCD Panel

LCD Size	13.3 inch Panel Size
Resolution	1920×1080 16:9
Brightness (cd/m ²)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)

[Click to Top](#)

15.6 INCH

► Introduction

The EPC-W15X2A series industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers versatile configuration options, equipped with onboard Intel® Celeron or advanced 10th/12th Gen Core™ i3/i5/i7 processors, delivering superior performance. Engineered for reliability, the EPC-W15X2A ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored

► Product Image



▶ System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

▶ I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0/ Type A	5	4	2	2	2	2	2	2
USB 3.0/ Type A	1	2	4	4	4	4	4	4
RS232/ DB9	4	4	4	4	4	4	4	4
RS485/ DB9	2	2	2	2	2	2	2	2
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

▶ Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

▶ Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

► Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

► OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

► Mechanical

Dimension	404.2(W)×253.5(D)×75.1(H)mm
Cutout Size	388.0×237.3mm
Weight	KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

► Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

► Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

► LCD Panel

LCD Size	15.6 inch Panel Size
Resolution	1920×1080 16:9
Brightness (cd/m ²)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)

[Click to Top](#) 18.5 INCH

► Introduction

The EPC-W18X2A series industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers versatile configuration options, equipped with onboard Intel® Celeron or advanced 10th/12th Gen Core™ i3/i5/i7 processors, delivering superior performance. Engineered for reliability, the EPC-W18X2A ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored

► Product Image



► System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

► I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0/ Type A	5	4	2	2	2	2	2	2
USB 3.0/ Type A	1	2	4	4	4	4	4	4
RS232/ DB9	4	4	4	4	4	4	4	4
RS485/ DB9	2	2	2	2	2	2	2	2
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

► Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

► Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

► Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

► OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

► Mechanical

Dimension	471.6(W)×291.9(D)×75.1(H)mm
Cutout Size	452.2×272.5mm
Weight	KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

► Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

► Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

► LCD Panel

LCD Size	18.5 inch Panel Size
Resolution	1920×1080 16:9
Brightness (cd/m ²)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)

[Click to Top](#)

21.5 INCH

► Introduction

The EPC-W21X2A series industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers versatile configuration options, equipped with onboard Intel® Celeron or advanced 10th/12th Gen Core™ i3/i5/i7 processors, delivering superior performance. Engineered for reliability, the EPC-W21X2A ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored

► Product Image



► System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

► I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0/ Type A	5	4	2	2	2	2	2	2
USB 3.0/ Type A	1	2	4	4	4	4	4	4
RS232/ DB9	4	4	4	4	4	4	4	4
RS485/ DB9	2	2	2	2	2	2	2	2
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

► Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

► Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

► Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

► OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

► Mechanical

Dimension	534.6(W)×326.1(D)×75.1(H)mm
Cutout Size	516.6×308.1mm
Weight	KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

► Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

► Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

► LCD Panel

LCD Size	21.5 inch Panel Size
Resolution	1920×1080 16:9
Brightness (cd/m ²)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)

[Click to Top](#)

23.6 INCH

► Introduction

The EPC-W24X2A series industrial PC showcases a fanless embedded design powered by CESIPC's proprietary LEGO MODE technology. It offers versatile configuration options, equipped with onboard Intel® Celeron or advanced 10th/12th Gen Core™ i3/i5/i7 processors, delivering superior performance. Engineered for reliability, the EPC-W24X2A ensures high functionality and meets rigorous protection standards, making it an optimal solution for mission-critical industrial applications.

- ★ Multi-platform, Multi-tier CPU options
- ★ Board-to-board Design for Stable Performance

- ★ LEGO MODE with Customizable Function Cards
- ★ i-Door Technology for Efficient, Tailored

► Product Image



▶ System Core

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
Cores	4	4	2	4	4	6	10	10
Threads	4	4	4	8	8	8	12	12
Frequency	2.0-2.4	2.0-2.6	2.1-4.1	1.6-4.2	1.8-4.9	1.2-4.4	1.3-4.4	1.1-4.7
Cache	2MB	1.5MB	4MB	6MB	8MB	10MB	12MB	12MB
TDP	10W	10W	15W	15W	15W	15W	15W	9W
Graphics	HD	UHD	UHD	UHD	UHD	UHD Graphics	Iris Xe	Iris Xe
Memory	4-8GB DDR3L	4-16GB DDR4	4-32GB DDR4			8-32GB DDR5		
Storage	1 x mSATA SSD		1 x mSATA/ 1 x M.2 SSD			2 x M.2 SSD		

▶ I / O Ports

CPU	Celeron J1900	Celeron J6412	i3-10110U	i5-10210U	i7-10510U	i3-1215U	i5-1235U	i7-1250U
USB 2.0/ Type A	5	4	2	2	2	2	2	2
USB 3.0/ Type A	1	2	4	4	4	4	4	4
RS232/ DB9	4	4	4	4	4	4	4	4
RS485/ DB9	2	2	2	2	2	2	2	2
VGA	1	1	1	1	1	1	1	1
HDMI	1	1	1	1	1	1	1	1
Ethernet	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210	2 x Intel I210
Audio	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS	3.5mm TRRS

▶ Power Supply

DC Input	1 × 3-pin Pluggable Terminal Block for 12V DC 9-36V DC Optional
Power Button	1x ATX Power On/Off Button
Booting	1x AT/ATX Mode Switch (Internal settings)

▶ Wireless Communication

Wi-Fi	Intel N6235 300Mbps, 802.11a/b/g/n, 2.4G / 5G
Wireless Network	4G LTE Full Netcom Module

► Environmental

Protection	Front Panel IP65 Compliant
Operating Temperature	0~50°C (-40~70°C Optional)
Storage Temperature	-10~60°C
Relative Humidity	10%~90% , Non-condensing

► OS

Windows	Windows 10 / Windows 11 Note: Celeron J1900 can support Windows 7
Linux	Ubuntu 16.04 / 18.04 / 20.04 / 22.04

► Mechanical

Dimension	589.3(W)×361.2(D)×75.1(H)mm
Cutout Size	562.7×338.4mm
Weight	KG N.W.
Material	6063 High-Strength Aluminum Alloy
Mechanical Construction	Aluminum Extrusion + Sheet Metal Structure
Mount	Wall Mount / VESA Mount
Clear CMOS Switch	1x Clear CMOS Switch

► Certs & Services

EMC	CE, FCC (According to EN 55032 & EN 55035) EN IEC 61000-3-2
Factory	ISO9001: 2015
ODM	BIOS / Boot on LOGO / OEM
MTBF	60,000 Hours

► Touch Panel

Touchscreen	Projected Capacitive Touch
Type	Resistive 5-wire (Optional)

► LCD Panel

LCD Size	23.6 inch Panel Size
Resolution	1920×1080 16:9
Brightness (cd/m ²)	300
Contrast Ratio	500 : 1
Backlight LED Life Time	50,000 hrs (LED Backlight)