


Incremental encoder-----GHS30 series

Application & Features:

Widely used in automatic control, automatic measurement, as the angle and speed sensors. ASIC devices internal, good reliability, long life, anti-jamming performance. Stainless steel shaft has a higher stability and protection. Metal shell is more solid and anti-impact. Bearing load heavy, anti-oil and water.

Model:




Electrical spec:

Output circuit	Open-collector output	Voltage output	Push-pull complementary outputs	driver
Supply voltage	5-26V	5-26V	5±0.25 5-26V	5±0.25 5-26V
Current consumption	≤80mA	≤80mA	≤80mA	≤150mA
Load current	40mA	40mA	40mA	60mA
Output high	Min Vcc*70%	Min Vcc-2.5V	Min Vcc-1.5V	Min 3.4V
Output low	MAX 0.4V	MAX 0.4V	MAX 0.8V	MAX 0.4V
Rise time Tr	MAX 1us	MAX 1us	MAX 1us	MAX 200ns
Fall time Tf	MAX 1us	MAX 1us	MAX 1us	MAX 200ns
Highest frequency response	100kHz	100kHz	100kHz	100kHz

Mechanical spec:

Max speed r/min	Starting torque	Axis maximum load	Impact	Anti-vibration
6000	<0.05Nm	Radial 15 N Axial 10N	50G/11ms	10G 10-2000Hz
Moment inertia	Work Temperature	Storage Temperature	Protection Degree	Weight
4 x 10.-8kgm ²	-25~80°C	-30~85°C	IP51	70g

Dimensions :



Output phase shift



Connections:

Signal	A	B	Z	A-	B-	Z-	Vcc	GND
Color	Green	White	Yellow	Brown	Grey	Orange	Red	Black
Without inverted signal	Green	White	Yellow	-	-	-	Red	Black